

Digital Indicator ID-S, IP53

Inch/Metric, 0,5", 0,00005", Lug Back

Item number: 543-795



Description

This is a standard model of indicator that is reliable and easy to use. The ABSOLUTE Digimatic Indicator ID-S offers you the following benefits:

- The ABSOLUTE sensor means you don't have to carry out origin setting every time you power it on, saving you time and hassle.
- You can access all functions by using the large, user-friendly buttons on the front of the indicator.
- Large character height of 9 mm provides good readability.
- Exceptional battery life.

Specification

Range:	0.5"/12.7 mm
No.	
Lug back plate:	
Range:	0,5" Inch
Digital step:	0,00005"/0,001 mm
Data output:	Yes
Max. Permissible Error (Total Range):	0,0001"/0,003 mm
Hysteresis:	0,0001"/0,002 mm
H MPE (Hysteresis):	0,0001"/0,002 mm
Mass:	150 g
Repeatability:	0,0001"/0,002 mm
Measuring force:	≤2,5 N N
Battery life:	approx. 18000 hours (0.001 mm type), approx. 20000 hours (0.01 mm type)
Protection:	IP53
Display:	LCD, character height 9 mm
Max. response speed:	Unlimited
Alarm:	Low voltage, counting value composition error
Stem Ø:	9,52 mm
Contact point:	Carbide ball, thread M 2.5 x 0.45 mm
Power supply:	1 battery SR-44
Delivered:	Including 1 battery
ON/OFF:	Yes
ORIGIN (ABS-Zero):	Yes
Low voltage alarm:	Yes
Counting direction switchable:	Yes
Digital/Analog:	Digital
Inch-Metric:	Inch/Metric
Type:	EN ISO Standard

Dimensions



938882

