



Digital Indicator ID-S, ANSI/AGD
Inch/Metric, 0,5", 0,0005", Flat Back
Item number: 543-783B



Description

This is a standard model of indicator that is reliable and easy to use.
The ABSOLUTE Digimatic Indicator ID-S offers you the following benefits:

- The ABSOLUTE sensor means you don't have to carry out origin setting every time you power it on, saving you time and hassle.
- You can access all functions by using the large, user-friendly buttons on the front of the indicator.
- Large character height of 9 mm provides good readability.
- Exceptional battery life.

Specification

Range:	0.5"/12.7 mm
No.	543-783
Lug back plate:	
Range:	0,5" Inch
Digital step:	0,0005"/0,01 mm
Data output:	Yes
Max. Permissible Error (Total Range):	0,001"/0,02 mm
Hysteresis:	0,001"/0,02 mm
H MPE (Hysteresis):	0,001"/0,02 mm
Mass:	140 g
Repeatability:	0,0005"/0,01 mm
Measuring force:	≤ 1,5 N
Mass lug/plain:	140/150 g
Battery life:	approx. 18000 hours (0.001 mm type), approx. 20000 hours (0.01 mm type)
Protection:	IP42
Display:	LCD, character height 9 mm
Max. response speed:	Unlimited
Alarm:	Low voltage, counting value composition error
Stem Ø:	9,52 mm
Contact point:	Carbide ball, thread # 4-48 UNF
Power supply:	1 battery SR-44
Delivered:	Including 1 battery
ON/OFF:	Yes
ORIGIN (ABS-Zero):	Yes
Low voltage alarm:	Yes
Counting direction switchable:	Yes
Digital/Analog:	Digital
Inch-Metric:	Inch/Metric
Type:	ASME/ANSI/AGD Standard

Dimensions





List Price

£16.32 inc. VAT

£13.60 ex. VAT



Silicon rubber boot for ID-C, ID-N, ID-S

238774

List Price

Spare parts

Consumable spares:



Battery SR44 1.5V

938882