

We measure it.



Temperature measuring instrument

testo 108 Thermometer
for fast, easy and precise
temperature measurements




Easy operation and handling

Instrument and probe waterproof (IP67)

Conform to HACCP and EN 13485

Lockable thermocouple probe



Temperature measurements are among the tasks carried out daily in the food sector. Only by taking precise measurements can the quality of the products be monitored and guaranteed. And it is the only way to fulfil the HACCP guidelines.

The thermometers from the product series testo 108 carry out spot check measurements in seconds. Whether in the transportation and storage of food, in restaurants, in large kitchens or in chain restaurants. The testo 108 is resistant to moisture and water, and thanks to the softcase (protective cover), is safe from impact damage and dirt.

Technical data

testo 108

testo 108, waterproof temperature instrument (Type T and K), incl. thermocouple probe type T, Softcase and calibration protocol

Part no. 0563 1080



testo 108-2

testo 108-2, waterproof temperature measuring instrument (Type T), incl. lockable thermocouple probe Type T, softcase and calibration protocol

Part no. 0563 1082



testo 108-2

- Screw-in probe lockable, provides absolutely secure attachment
- Auto-hold, hold and min./max. function

Sensor type

Measurement unit	Temperature °C
Connectable sensor types	Thermocouple Type T and Type K (testo 108) Thermocouple Type T (testo 108-2)
Meas. range	-50 to +300 °C
Accuracy Instrument (Ambient temperature +23 °C ±3 °C)	±0.5 °C (-30 to +70 °C) ±0.5 °C ±0.5 % of mv (remaining range)
Accuracy Probes	±0.5 °C (-40 to -20 °C) ±0.2 °C (-20 to +70 °C) ±0.5 °C (+70 to +125 °C) ±0.4 % of mv (+125 to +300 °C)
Resolution	0.1 °C

General technical data

Oper. temp.	-20 to +60 °C
Storage temp.	-30 to +70 °C
Protection class	IP67 (with delivered probe connected)
Measurement rate	2 measurements per second
Adjustment time t_{99}	10 s (in moving liquid)
Display	LCD, one-line, with status line
Standard	EN 13485
EC guideline	2004/108/EG
Power supply	3 x battery Type AAA
Battery life	2500 h (typical, at 23 °C)
Features	Auto-hold, hold and min./max. function (testo 108-2)
Warranty	2 years Warranty conditions: see www.testo.com/warranty

Testo Limited
Newman Lane
Alton, Hampshire
GU34 2UR

01420 544433
01420 544434

