

Absolute pressure measuring instrument

testo 511 - Pocket-sized absolute pressure measurement

Highly accurate absolute pressure measurement to ±3 hPa

Barometric altitude measurement

Calculation of barometric air pressure

8 available pressure units

Display illumination





Illustration 1:1

testo 511 measures absolute pressure to an accuracy of ± 3 hPa. The measuring instrument is ideal for absolute pressure compensation during flow velocity measurements with a Pitot tube, for example. By entering the altitude above sea level, this is converted into barometric air pressure. In addition to this, a barometric pressure measurement between two points is also possible. The eight switchable pressure units offer the user highest flexibility in measurement.

The clip-on protective cap, wrist strap and belt holder ensure safekeeping of the instrument. testo 511 is very handy, small and easy to use.

www.testo.co.uk



Technical data / Accessories

testo 511

testo 511; absolute pressure meter incl. protective cap, batteries and calibration certificate

Part no. 0560 0511



Sensor type	Absolute pressure probe
Meas. range	300 to 1200 hPa
Accuracy ±1 digit	±3.0 hPa
Resolution	0.1 hPa

General technical data

Selectable units	hPa, mbar, Pa, mmH2O, mmHg, inH2O, inHg, psi, m, ft	
Measurement rate	0.5 s	
Storage temp.	-40 to +70 °C	
Oper. temp.	0 to +50 °C	
Battery type	2 batteries Type AAA	
Battery life	200 h (average, without display illumination)	
Protection class	IP40	
Weight	90 g (with batteries and protective cap)	
Dimensions	119 x 46 x 25 mm (incl. protective cap)	
Warranty	2 years	

Accessories Part no.

Accessories for measuring instrument

Connection hose, silicone, 2 m long, max. load 700 hPa (mbar)		
ISO calibration certificate relative pressure, 3 measurement points distributed over the measurement range		
ISO calibration certificate pressure, differential pressure, accuracy 0.1 to 0.6 (% of fsv)		