# KERN EOC 60K-3A







Measuring system	
Adjustment options:	External calibration
Linearisation (points):	3
Linearity:	15 g
Readability [d]:	5 g
Recommended adjusting weight:	60 kg (M1)
Repeatability:	5 g
Resolution:	12000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-60000000 mg
Warm up time:	30 min
Weighing capacity [Max]:	60 kg
Weighing system:	Strain gauge
Weighing units:	g kg lb oz

lare range:	-60000000 mg
Warm up time:	30 min
Weighing capacity [Max]:	60 kg
Weighing system:	Strain gauge
Weighing units:	g kg lb oz
D'I.	

Display digit height:

Counting	
Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	2 g
Mininum piece weight at piece counting (Normal):	20 g

2,400 cm

Functions		
Counting function:	yes	
Percentage determination:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

r ower suppry	
Charging time:	3 h
Input voltage:	100V-240V 0.4A
Mains adapter/adapter included:	CHELIBOTIKTIS

n/a:	Mains adapter external
Power supply	
Operating time (Backlight off):	43 h
Operating time (Backlight on):	26 h

Rechargeable battery:	Rchrg. battery optional -
	intern

Service

Adjustment at the location of installation: 961-249		
DAkkS Certificate:	963-129	
Category		

Category	
Brand:	KERN
Category:	Balances
Product Group:	Industiral scale

Packaging & snipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	720 x 360 x 185 mm
Gross weight:	7,500 kg
Net weight:	5,200 kg
Shipping method:	Parcel service

Construction	
Cable length of display device:	3 m
Dimensions of display device (WxDxH):	268 x 115 x 65 mm
Dimensions of weighing plate (WxDxH):	300 x 300 x 110 mm
of stand:	33 cm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	300 x 300 mm

## KERN EOC 60K-3A



All-round parcel scale with practical Flip/Flop display device for greatest ease of use

## Piktogramme

### STANDARD



#### **OPTION**

