KERN **EOC 60K-3L**

All-round parcel scale with practical Flip/Flop display device for greatest ease of use

Measuring system

Adjustment options:	External calibration
Linearisation (points):	3
Linearity:	3 g | 6 g
Readability [d]:	1 g | 2 g
Recommended adjusting weight:	50 kg (F2)
Repeatability:	1 g | 2 g
Resolution:	30 30.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-60000000 mg
Warm up time:	2 h | 2 h
Weighing capacity [Max]:	30 kg | 60 kg
Weighing system:	Strain gauge
Weighing units:	g kg lb oz

Display

Display digit height:	2,400 cm

Counting

Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	2 g
Mininum piece weight at piece counting (Normal):	20 g

Functions

Counting function:	yes
Percentage determination:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes

Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply

Charging time:	3 h
Input voltage:	100V-240V 0.4A
Mains adapter/adapter included:	CH EURO UK US

n/a:	Mains adapter external

Power supply

Operating time (Backlight off):	43 h
Operating time (Backlight on):	26 h
Rechargeable battery:	Rchrg. battery optional - intern

Service

Adjustment at the location of installation:	961-249
DAkkS Certificate:	963-129

Category

Brand:	KERN
Category:	Balances
Product Group:	Industiral scale

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	880 x 490 x 160 mm
Gross weight:	12,500 kg
Net weight:	9 kg
Shipping method:	Parcel service

Construction

Cable length of display device:	3 m
Dimensions of display device (WxDxH):	268 x 115 x 80 mm
Dimensions of weighing plate (WxDxH):	500 x 400 x 120 mm
of stand:	33 cm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	500 x 400 mm

KERN **EOC 60K-3L**

All-round parcel scale with practical Flip/Flop display device for greatest ease of use

KERN®

Piktogramme

STANDARD

CAL EXT	RS 232	KCP PROTOCOL	GLP PRINTER	PCS	SUM A	PERCENT %	TOL	MOVE
IP 65	MULTI B	DMS	1 DAY					

OPTION

ACCU	DAkkS +3 DAYS