KERN SXS30K-2M



Stainless steel platform scale with stainless steel IP68 display and EC type approval [M]



Measuring system			
Adjustment options:	External calibration		
Linearity:	5g 10g		
Readability [d]:	5 g 10 g		
Recommended adjusting weight:	30 kg (M1)		
Repeatability:	5 g 10 g		
Resolution:	3 3.000		
Stabilisation time under laboratory conditions:	2 s		
Tare range:	-30 kg		
Warm up time:	10 min 10 min		
Weighing capacity [Max]:	15 kg 30 kg		
Weighing system:	Strain gauge		
Weighing units:	kg		
Display			
Display digit height:	5,500 cm		
Technical data about verification			
Minimum load [Min]:	100 g 200 g		
Periodic Verification for Italy:	969-112		
	909-112		
Verification approval conforming to 2014/31/EU:	yes		
to 2014/31/EU:	yes		
to 2014/31/EU: Verification by KERN possible:	yes		
to 2014/31/EU: Verification by KERN possible: Verification class:	yes III		
to 2014/31/EU: Verification by KERN possible: Verification class: Verification value [e]:	yes III		
to 2014/31/EU: Verification by KERN possible: Verification class: Verification value [e]: Counting	yes JII 5 g 10 g		

Mininum piece weight at piece

counting (Normal):

Functions			
Counting function:	yes		
Data hold function:	yes		
Peak function:	yes		
PRE-TARE function:	yes		
Vibration-free weighing (Animal weighing program):	yes		
Weighing with tolerance range:	yes		
Environmental conditions			
Maximum humidity:	80 %		
Maximum operating temperature:	40 °C		
Minimum ambient temperature:	-10 °C		
Minimum humidity:	0%		
Power supply			
	40.5		
Charging time:	12h		
Input voltage:	220 V - 240 V AC 50 Hz		
Mains adapter/adapter included:	EURO		
Operating time (Backlight off):	80 h		
Operating time (Backlight on):	40 h		
Rechargeable battery:	Rchrg. battery optional		
	(factory)		
Service			
Service Adjustment at the location of installation	n:961-248		
	n: 961-248 963-128		
Adjustment at the location of installation			
Adjustment at the location of installation DAkkS Certificate:	963-128		
Adjustment at the location of installation DAkkS Certificate: Verification:	963-128		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand:	963-128 965-228 KERN		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category:	963-128 965-228 KERN Balances		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group:	963-128 965-228 KERN		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category:	963-128 965-228 KERN Balances		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group:	963-128 965-228 KERN Balances		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping	963-128 965-228 KERN Balances Industiral scale		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery:	963-128 965-228 KERN Balances Industiral scale		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	963-128 965-228 KERN Balances Industiral scale 24 h 630 x 510 x 220 mm		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	963-128 965-228 KERN Balances Industiral scale 24 h 630 x 510 x 220 mm 13,400 kg		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	963-128 965-228 KERN Balances Industiral scale 24 h 630 x 510 x 220 mm 13,400 kg 11,800 kg		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	963-128 965-228 KERN Balances Industiral scale 24 h 630 x 510 x 220 mm 13,400 kg 11,800 kg Parcel service		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device:	963-128 965-228 KERN Balances Industiral scale 24 h 630 x 510 x 220 mm 13,400 kg 11,800 kg Parcel service		
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	963-128 965-228 KERN Balances Industiral scale 24 h 630 x 510 x 220 mm 13,400 kg 11,800 kg Parcel service		

10 g

KERN SXS30K-2M



Stainless steel platform scale with stainless steel IP68 display and EC type approval [M]

Level indicator:	yes		
Material weighing plate:	stainless steel		
Revolving screw feet:	yes		
Wall mount:	yes		
Weighing surface (WxD):	400 x 300 mm		

Piktogramme

STANDARD

GLP			^-	666	=		
CAL EXT PRINTER	PCS	TOL	MOVE	IP 68	INOX	230 V	DMS

1 DAY

OPTION

III)	DAkk	
ACCU	+3 DAYS	

FACTORY

• 6882.•	• 6884 •	୲ୡ	Μ
RS 232	RS 485	BT	+3 DAYS