KERN SXS10K-3M



Stainless steel platform scale with stainless steel IP68 display and EC type approval [M]



Measuring system	
Adjustment options:	External calibration
Linearity:	2 g 5 g
Readability [d]:	2 g 5 g
Recommended adjusting weight:	15 kg (M1)
Repeatability:	2 g 5 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-15 kg
Warm up time:	10 min 10 min
Weighing capacity [Max]:	6 kg 15 kg
Weighing system:	Strain gauge
Weighing units:	kg
Display	
Display digit height:	5,500 cm
Technical data about verification	
Minimum load [Min]:	40 a 100 a

Minimum load [Min]:	40 g 100 g
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	2 g 5 g
Counting	
Counting resolution:	30000

Counting resolution:	30000
Mininum piece weight at piece	500 mg
counting (Laboratory:	
Mininum piece weight at piece counting (Normal):	5 g

Functions					
Counting function:	yes				
Data hold function:	yes				
Peak function:	yes				
PRE-TARE function:	yes				
Vibration-free weighing (Animal weighing program):	yes				
Weighing with tolerance range:	yes				
Environmental conditions					
Maximum humidity:	80 %				
Maximum operating temperature:	40 °C				
Minimum ambient temperature:	-10 °C				
Minimum humidity:	0 %				
Power supply					
Charging time:	12 h				
Input voltage:	220 V - 240 V AC 50 Hz				
1 8	EURO				
Mains adapter/adapter included:					
Operating time (Backlight off):	80 h				
Operating time (Backlight on):	40 h				
Rechargeable battery:	Rchrg. battery optional (factory)				
Service					
Service Adjustment at the location of installation	1:961-248				
	963-128				
Adjustment at the location of installation					
Adjustment at the location of installation DAkkS Certificate:	963-128				
Adjustment at the location of installation DAkkS Certificate: Verification:	963-128				
Adjustment at the location of installation DAkkS Certificate: Verification: Category	963-128 965-228				
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand:	963-128 965-228 KERN				
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category:	963-128 965-228 KERN Balances				
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping	963-128 965-228 KERN Balances				
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery:	963-128 965-228 KERN Balances Industiral scale				
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	963-128 965-228 KERN Balances Industiral scale 24 h 498 x 570 x 221 mm				
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	963-128 965-228 KERN Balances Industiral scale 24 h 498 x 570 x 221 mm 8,228 kg				
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	963-128 965-228 KERN Balances Industiral scale 24 h 498 x 570 x 221 mm 8,228 kg 6,302 kg				
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	963-128 965-228 KERN Balances Industiral scale 24 h 498 x 570 x 221 mm 8,228 kg				
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	963-128 965-228 KERN Balances Industiral scale 24 h 498 x 570 x 221 mm 8,228 kg 6,302 kg				
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	963-128 965-228 KERN Balances Industiral scale 24 h 498 x 570 x 221 mm 8,228 kg 6,302 kg				
Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	963-128 965-228 KERN Balances Industiral scale 24 h 498 x 570 x 221 mm 8,228 kg 6,302 kg Parcel service				

KERN SXS10K-3M



Stainless steel platform scale with stainless steel IP68 display and EC type approval [M]

Level indicator:	yes		
Material weighing plate:	stainless steel		
Revolving screw feet:	yes		
Wall mount:	yes		
Weighing surface (WxD):	300 x 240 mm		

Piktogramme

STANDARD

	GLP			<u>∧-</u>	666	=		
CAL EXT	PRINTER	PCS	TOL	MOVE	IP 68	INOX	230 V	DMS

1 DAY

OPTION

III)	DAkks		
ACCU	+3 DAYS		

FACTORY

• 6884	• 6884 •	୲ୡ	Μ
RS 232	RS 485	BT	+3 DAYS